

Project Name:Spot light(1pcs)

Product/Part number: TR0140W 12W

Comment/Result: PASS

Project ID:20211025

Date:Oct-25th-2021

	_	_			TR0140W			
No.	Bran d	Item No.	Mode①	Mode ⁽²⁾	12W/230V			
					Max	Min	Description	
				Progressive switch-off	12.64W	2.36W	Stable dimming performance and invisible flicker, but there is faint flicker when turn on; The light can be dimmed to 5%.	
			Fluocompact*	Night light	12.65W	2.28W	Stable dimming performance and invisible flicker, but there is faint flicker when turn on; The light can be dimmed to 5%.	
			Theocompute	100%	12.63W	2.47W	Stable dimming performance and invisible flicker, but there is faint flicker when turn on; The light can be dimmed to 5%.	
				No Funciton	12.6W	2.47W	Stable dimming performance and invisible flicker,but there is faint flicker when turn on;The light can be dimmed to 5%.	
				Progressive switch-off	12.58W	1.43W	Stable dimming performance and invisible flicker,but there is faint flicker when turn on;The light can be dimmed to 5%.	
			Capacitive	Night light	12.75W	1.42W	Stable dimming performance and invisible flicker,but there is faint flicker when turn on;The light can be dimmed to 5%.	
			loads(CFL)	100%	12.43W	1.6W	Stable dimming performance and invisible flicker,but there is faint flicker when turn on;The light can be dimmed to 5%.	
				No Funciton	12.52W	1.44W	Stable dimming performance and invisible flicker,but there is faint flicker when turn on;The light can be dimmed to 5%.	
				Progressive switch-off	12.94W	1.52W	Stable dimming performance and invisible flicker,but there is faint flicker when turn on;The light can be dimmed to 5%.	



Project Name:Spot light(1pcs)

Product/Part number: TR0140W 12W

Comment/Result: PASS

Project ID:20211025

Date:Oct-25th-2021

						TR0140W			
No.	Bran d	Item No.	Mode①	ode(1) Mode(2)		12W/230V			
					Max	Min	Description		
			Inductive loads	Night light	12.98W	1.48W	Stable dimming performance and invisible flicker, but there is faint flicker when turn on; The light can be dimmed to 5%.		
				100%	12.98W	1.49W	Stable dimming performance and invisible flicker,but there is faint flicker when turn on;The light can be dimmed to 5%.		
				No Funciton	12.96W	1.51W	Stable dimming performance and invisible flicker,but there is faint flicker when turn on;The light can be dimmed to 5%.		
	ha		LED load	Progressive switch-off	12.87W	2.32W	Stable dimming performance and invisible flicker, but there is faint flicker when turn on; The light can be dimmed to 5%.		
1		EVN		Night light	12.93W	2.25W	Stable dimming performance and invisible flicker, but there is faint flicker when turn on; The light can be dimmed to 5%.		
	hager	1012		100%	12.91W	2.21W	Stable dimming performance and invisible flicker,but there is faint flicker when turn on;The light can be dimmed to 5%.		
				No Funciton	12.83W	2.23W	Stable dimming performance and invisible flicker, but there is faint flicker when turn on; The light can be dimmed to 5%.		
				Progressive switch-off	12.47W	2W	Stable dimming performance and invisible flicker,but there is faint flicker when turn on;The light can be dimmed to 5%.		
			Load	Night light	12.44W	1.98W	Stable dimming performance and invisible flicker,but there is faint flicker when turn on;The light can be dimmed to 5%.		



Project Name:Spot light(1pcs)

Product/Part number: TR0140W 12W

Comment/Result: PASS

Project ID:20211025

Date:Oct-25th-2021

							TR0140W		
No.	Bran d	Item No.	Mode①	Mode ⁽²⁾	12W/230V				
					Max	Min	Description		
			ED)	100%	12.41W	1.68W	Stable dimming performance and invisible flicker,but there is faint flicker when turn on;The light can be dimmed to 5%.		
				No Funciton	12.43W	1.69W	Stable dimming performance and invisible flicker,but there is faint flicker when turn on;The light can be dimmed to 5%.		
				Progressive switch-off	12.6W	1.45W	Stable dimming performance and invisible flicker,but there is faint flicker when turn on;The light can be dimmed to 5%.		
			Factory reset	Night light	12.43W	1.46W	Stable dimming performance and invisible flicker,but there is faint flicker when turn on;The light can be dimmed to 5%.		
				100%	12.42W	1.45W	Stable dimming performance and invisible flicker,but there is faint flicker when turn on;The light can be dimmed to 5%.		
				No Funciton	12.4W	1.43W	Stable dimming performance and invisible flicker,but there is faint flicker when turn on;The light can be dimmed to 5%.		
2	hager	EVN011			12.52W	1.4W	Stable dimming performance and invisible flicker,but there is faint flicker when turn on;The light can be dimmed to 5%.		
		Π	EC1				Incompatible		
		ΠD	EC2				Incompatible		
3	eltako	12N	LC1				Incompatible		
	ó	EUD12NPN-UC	LC2				Incompatible		
		.UC	LC3				Incompatible		
			EUD		11.82W		Can be turned on but Non-dimmable		



Project Name:Spot light(1pcs)

Product/Part number: TR0140W 12W

Comment/Result: PASS

Project ID:20211025

Date:Oct-25th-2021

					TR0140W				
No.	Bran d	Item No.	Mode①	Mode ²	12W/230V				
					Max	Min	Description		
			RTD				Incompatible		
			ESV		11.84W		Can be turned on&off but Non-dimmable and invisible flicker; Time switch Funciton is available.		
		EU	TLZ		11.6W		Can be turned on&off but Non-dimmable and invisible flicker; Time switch Funciton is available.		
4	eltako	EUD12D-UC	MIN		11.94W		Can be turned on&off but Non-dimmable.		
			MMX		11.65W		Can be turned on&off but Non-dimmable.		
			ΤI				Incompatible		
			ER				Incompatible		
			ON		11.93W		Funciton is available		
			OFF				Funciton is available		
			1		11.9W	1.17W	Unstable dimming performance and there is visible flicker.		
			2		11.84W	0.52W	Stable dimming performance and invisible flicker.The light can be turned off in the Min position.		
	S	CC	3 Prog				Incompatible		
5	schneider	CCTDD20016	4 LED2		11.86W	0.13W	Stable dimming performance and invisible flicker.The light can be turned off in the Min position.		
		6	5 Prog		10.33W	0.08W	Unstable dimming performance and invisible flicker;The light can be turned off in the Min position.		



Project Name:Spot light(1pcs)

Product/Part number: TR0140W 12W

Comment/Result: PASS

Project ID:20211025

Date:Oct-25th-2021

							TR0140W		
No.	Bran d	Item No.	Mode①	Mode ²	12W/230V				
					Max	Min	Description		
			6 Strd		10.85W		Can be turned on&off but Non-dimmable;Invisible flicker.		
			7 ON		11.83W		Can be turned on but Non-dimmable;Funciton is available.		
				Green	12.68W	1.89W	Stable dimming performance and invisible flicker. The light can be dimmed to 5%.		
				Orange	11.85W		Can be turned on&off but Non-dimmable;Invisible flicker.		
	Legr	00;	White 002671	White	12.66W	1.95W	Stable dimming performance and invisible flicker. The light can be dimmed to 5%.		
6	Legrandoc	2671		Blue	10.82W		Can be turned on&off but Non-dimmable;Invisible flicker.		
				Red	12.57W	3.55W	Can only be dimmed to the Min position;Invisible flicker.		
			Red		\geq	\geq			
			Green		\triangleright	\geq			
			Orange Blue		\geq	\geq			
			1		11.84W	1.93W	Stable dimming performance and invisible flicker. The light can be dimmed to 5%.		
			2				Incompatible		
			CFLI1		12.25W	1.63W	Stable dimming performance and invisible flicker. The light can be dimmed to 5%.		
	Z	310-(CFLI2		12.78W	2.63W	Stable dimming performance and invisible flicker.The light can be dimmed to 5%.		
7	Niko	310-00700	LED1		11.89W	0.26W	Stable dimming performance and invisible flicker.The light can be turned off in the Min position.		
			LED2		11.96W	0.21W	Stable dimming performance and invisible flicker.The light can be turned off in the Min position.		



Project Name:Spot light(1pcs)

Project ID:20211025

Product/Part number: TR0140W 12W

Comment/Result: PASS

Date:Oct-25th-2021

						TR0140W			
No.	Bran d	Item No.	Mode①	Mode ⁽²⁾		-	12W/230V		
					Max	Min	Description		
			LED3		11.85W	0.26W	Stable dimming performance and invisible flicker.The light can be turned off in the Min position.		
			LED4		11.92W	0.2W	Stable dimming performance and invisible flicker.The light can be turned off in the Min position.		
8	NiKO	310-04900			11.98W	1.7W	Stable dimming performance and invisible flicker. The light can be dimmed to 5%.		
9	NiKO	310-02800			12.55W	0.91W	Stable dimming performance and invisible flicker.The light can be dimmed to 5%.		
			DEFAULT 1		12.71W	1.82W	Stable dimming performance and invisible flicker.The light can be dimmed to 5%.		
			HALO LED2		12.71W	1.69W	Stable dimming performance and invisible flicker.The light can be dimmed to 5%.		
			Transformer LED3		12.69W	0.93W	Stable dimming performance and invisible flicker. The light can be dimmed to 5%.		
10	NiK	310-02	LED4		9.28W	0.54W	Stable dimming performance but the range is limited.But there is visible flicker in the Min position.		
	Ś)2900	Transformer LED5		12.12W	0.52W	Stable dimming performance and invisible flicker.The light can be dimmed to 5%.		
			LED6		12.72W	0.37W	Stable dimming performance and invisible flicker.The light can be turned off in the Min position.		
			LED7		12.09W	0.5W	Stable dimming performance and invisible flicker. The light can be dimmed to 5%.		
			LED8		12.69W	0.38W	Stable dimming performance and invisible flicker.The light can be turned off in the Min position.		



Project Name:Spot light(1pcs)

Product/Part number: TR0140W 12W

Comment/Result: PASS

Project ID:20211025

Date:Oct-25th-2021

							TR0140W
No.	Bran d	Item No.	Mode①	Mode ⁽²⁾			12W/230V
				<u> </u>	Max	Min	Description
			LED1		11.81W	1.33W	Stable dimming performance and invisible flicker. The light can be dimmed to 5%.
			LED2				Incompatible
			LED3 *		12.19W	1.63W	Stable dimming performance and invisible flicker. The light can be dimmed to 5%.
	Z	310-	LED4*		12.8W	2W	Stable dimming performance and invisible flicker. The light can be dimmed to 5%.
11	NiKO	310-01900	LED5		11.82W	0.26W	Stable dimming performance and invisible flicker.The light can be turned off in the Min position.
			LED6		13.04W	0.19W	Stable dimming performance and invisible flicker.The light can be turned off in the Min position.
			LED7*		11.77W	0.32W	Stable dimming performance and invisible flicker. The light can be dimmed to 5%.
			LED8*		13.07W	0.18W	Stable dimming performance and invisible flicker.The light can be turned off in the Min position.
			Preset levels mode		12.13W	2.51W	Can be turened on but Non-dimmable;Invisible flicker.
12	bticino	N4411N	Preset levels mode+night		12.13W	2.5W	Can be turened on but Non-dimmable;Invisible flicker.
	no	11N	Dimming mode		12.12W	1.42W	Stable dimming performance and invisible flicker. The light can be dimmed to 5%.
13	bticino	N4408N					Incompatible
			LED1		12.74W	2.01W	Stable dimming performance and invisible flicker. The light can be dimmed to 5%.
			HALO LED2				Incompatible



Project Name:Spot light(1pcs)

Project ID:20211025

Product/Part number: TR0140W 12W

Comment/Result: PASS

Date:Oct-25th-2021

						TR0140W				
No.	Bran d	Item No.	Mode①	Mode ⁽²⁾		12W/230V				
				,	Max	Min	Description			
			Transformer LED3*				Incompatible			
14	NiKO	310-03900	LED4		9.19W	0.56W	Stable dimming performance but the range is limited.But there is visible flicker in the Min position.			
	0	006	Transformer LED5		12W	0.62W	Stable dimming performance and invisible flicker. The light can be dimmed to 5%.			
			LED6		12.75W	0.5W	Stable dimming performance and invisible flicker.The light can be turned off in the Min position.			
			LED7*		11.97W	0.59W	Stable dimming performance and invisible flicker.The light can be dimmed to 5%.			
			LED8*		12.71W	0.51W	Stable dimming performance and invisible flicker.The light can be turned off in the Min position.			
45	elta	UD61N	P-AB		12.11W	1.03W	Stable dimming performance and invisible flicker. The light can be dimmed to 5%.			
15	eltako	UD61NPL-230	P-AN		12.98W	0.94W	Stable dimming performance and invisible flicker.The light can be turned off in the Min position.			
16	eltako	EUD61NP-230V					Incompatible			
			AUTO		11.8W	1.18W	Stable dimming performance and invisible flicker;Slow dimming response and can't be turned off in the Min position.			
		Ш	LC1		12.74W	0.96W	Stable dimming performance and invisible flicker;Slow dimming response and can't be turned off in the Min position.			



Project Name:Spot light(1pcs)

Product/Part number: TR0140W 12W

Comment/Result: PASS

Project ID:20211025

Date:Oct-25th-2021

					TR0140W				
No.	Bran d	Item No.	Mode①	Mode ²	12W/230V				
					Max	Min	Description		
17	eltako	UD61NPN-230V	LC2		12.7W	0.95W	Stable dimming performance and invisible flicker;Slow dimming response and can't be turned off in the Min position.		
		230V	LC3		12.65W	0.94W	Stable dimming performance and invisible flicker;Slow dimming response and can't be turned off in the Min position.		
			EC1		11.77W	1.83W	Unstable dimming performance and invisible flicker.		
			EC2		11.79W	1.81W	Unstable dimming performance and invisible flicker.		
			AUTO		12.22W	1.2W	Stable dimming performance and invisible flicker;Slow dimming response and can't be turned off in the Min position.		
			LC1		12.72W	0.92W	Stable dimming performance and invisible flicker;Slow dimming response and can't be turned off in the Min position.		
	elt	EUD61NPN-UC	LC2		12.77W	0.95W	Stable dimming performance and invisible flicker;Slow dimming response and can't be turned off in the Min position.		
18	eltako		LC3		12.72W	0.93W	Stable dimming performance and invisible flicker;Slow dimming response and can't be turned off in the Min position.		
		C	EC1		11.79W	1.76W	Unstable dimming performance and invisible flicker;Slow dimming response and can't be turned off in the Min position.		
			EC2		11.76W	1.74W	Unstable dimming performance and invisible flicker;Slow dimming response and can't be turned off in the Min position.		



Project Name:Spot light(1pcs)

Project ID:20211025

Product/Part number: TR0140W 12W

Date:Oct-25th-2021

Comment/Result: PASS

Inspector:Tuan&James

			TR0140W				
No.	Bran d	Item No.	Mode①	Mode ²		12W/230V	
					Max	Min	Description

Test result: TThe ones with better compatibility are: No. 5 (Mode 2; 4LED2)/No.6(White Mode: Grenn, White)/No.7(1,CFLI1,CFLI2,LED1, LED2,LED3,LED4 Mode)/No.8/9/10(DEFAULT 1,HALO LED2,Transformer LED3,Transformer LED5, LED6,LED7, LED8 Mode)/No.11(LED1, LED3*, LED4*, LED5, LED6, LED7*, LED8*Mode)/No.12 (Dimming mode) /No.14(LED 1, Transformer LED5, LED6, LED7*, LED8* mode)/No.15/17(AUTO, LC1,LC2,LC3, Mode)/No.18(AUTO, LC1,LC2,LC3, Mode)

